

LEVEL 6

Fixed

Aluminum Van-Guard® Security Screen

Model: A-VNG-Z

PART 1 GENERAL

1.01 Description

The security screens shown on the plans and herein specified are the products of Kane Innovations, Erie, Pennsylvania. This manufacturer's name and products have been used to establish the standards of construction and quality of workmanship required for this project. Manufacturers bidding on this project must be actively engaged in the fabrication of specified items for a minimum of five (5) years prior to the bid date. Manufacturers requesting approval to bid their products as equal must submit to the Architect full-size drawings, including details of construction, and a complete operating security screen sample, ten (10) days prior to the bid date.

1.02 Submittals

- A. Manufacturer shall submit shop drawings, showing details of attachment to surround materials and elevations showing scope of the project.
- B. Samples of materials may be requested without cost to owner: frame sections, infill sections, fasteners, mullion section, corner section, etc.

1.03 Warranty

The operation of the security screen supplied by Kane Innovations on the designated project is warranted for one (1) year against any proven defective material or parts, as called for in the specifications and approved shop drawings. This warranty does not cover abuse by others.

PART 2 PRODUCTS

2.01 Acceptable Manufacturers

Kane Innovations, Erie, PA
☎ (800) 773-2439

2.02 Main Frame

- A. The main frame shall be of channel design measuring 1.25"[31.75mm] x 2.875"[73.025mm] x 0.75"[19.05mm], extruded from 6063-T6-aluminum alloy. Weight shall be not less than .927 lbs./ft., with a nominal thickness of .125-inch. The corners of the main frame shall be mitered and internally robotically welded.
- B. A removable interlocking concealment cover (Z-shaped) measuring 2.094"[53.181] x 0.50"[12.70] x 0.625"[15.875], extruded from 6063-T6 aluminum alloy, .062-inch thick, .290 lbs./ft., shall be attached to the main frame using TORX® tamper-resistant screws. Braces shall be furnished when required.

2.03 Finish

- A. The aluminum shall be thoroughly cleaned in a 5-step bonderizing process. An electrostatically applied thermoplastic, polyester powder coating (2.5 mil min. thickness) which shall be applied and baked to a hard mar-resistant finish in one of Kane's standard colors.
 - White
 - Gray
 - Black
 - Beige
 - Dark Bronze
 - Custom colors are available at additional cost with submission of color sample.
- B. Anodized finish options:
 - Clear anodize (215-R1)

2.04 Wire Cloth

- Wire cloth shall be woven 12-mesh to the inch from .028-inch diameter Type 304 stainless steel wire and double crimped.
- Wire cloth shall be woven 10-mesh to the inch from .047-inch diameter Type 304 stainless steel wire and double crimped.

Perforated Panel

- 18-gauge stainless steel with 63% open area
- 16-gauge mill-galvannealed steel with 63% open area
- 14-gauge mill-galvannealed steel with 51% open area
- 12-gauge mill-galvannealed steel with 51% open area

2.05 Infill Attachment

- A. The wire cloth shall be folded 90 degrees and held securely in place by means of a removable interlocking concealment plate and TORX® tamper-resistant screws.
- B. The perforated panel shall lie flat on the main frame and be held in place by means of a removable interlocking concealment plate and TORX® tamper-resistant screws.
- C. TORX® tamper-resistant screws shall penetrate the removable interlocking concealment plate, wire cloth and main frame approximately 4" [101.6] on center.

2.06 Hardware

- A. Each screen shall include .125-inch thick aluminum back-up angles. The 1" [25.40] x 2" [50.80] angles shall be supplied at the head and jambs if required.
- B. Each screen shall come fully assembled and tested at the factory for operation.

PART 3 EXECUTION

3.01 Inspection

Verify that openings fit allowable tolerances, are plumb, level, provide a solid anchoring surface and comply with approved shop drawings.

3.02 Installation

- A. Install in accordance with approved shop drawings and specifications.
- B. Plumb and align faces in a single plane and erect screens square and true, adequately anchored to structure.
- C. After completion of installation, screens shall be adjusted and cleaned.

PART 4 ENVIRONMENTAL REPORTING

4.01 LEED Materials and Resources

- A. Recycled Content: This product contributes toward satisfying Credit 4 under LEED.
- B. Regional Material: This product can contribute toward satisfying Credit 5 under LEED.